

New



Metallic Red

Racing Blue



Darknight

Thunder Grey



Specifications

Engine

Engine type	Liquid-cooled, 4-stroke, SOHC, 4-valve
Displacement	155 CC
Bore & stroke	58.0 mm x 58.7 mm
Compression ratio	11.6 : 1
Maximum horse power	13.7kW (18.6PS)/10000 RPM
Maximum torque	14.1 Nm (1.4 kgf·m) @8,500 RPM
Starting system type	Electric starter
Transmission type	Constant mesh, 6-speed
Clutch type	Wet, multiple-disc
Fuel system	Fuel injection

Chassis

Frame type	Deltabox
Front suspension system	Telescopic fork
Rear suspension system	Monocross (link suspension)
Brake type (Front)	Disc brake (282 mm)
Brake type (Rear)	Disc brake (220 mm)
Front tire	100/80-17M/C 52P - Tubeless
Rear tire	140/70R17M/C 66H - Radial Tubeless
Inner tube (diameter of front fork)	41.0 mm

Dimensions

Overall Length	1,990 mm
Overall Width	725 mm
Overall Height	1,135 mm

Dimensions

Seat height	815 mm
Wheel base	1,325 mm
Minimum ground clearance	170 mm
Weight (with oil & a full fuel tank)	142 kg
Fuel tank capacity	11 L

Other Information

Battery	12V, 4.0Ah
Headlight	LED
Auxiliary light	LED
Brake/tail light	LED
Speedometer	Digital
Tachometer	Digital
Fuel gauge	Digital
Gear position indicator	Equipped
Fuel consumption indicator	Equipped
Shift timing light	Equipped
VVA indicator	Equipped
Clock	Digital
VVA	Equipped
Side stand engine cut off switch	Equipped
Dual horn	Equipped
ABS	Dual channel ABS



5 YEAR WARRANTY
Up to 10,00,000 kms mileage warranty**



Authorized Dealer

*The specifications and design of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colours shown may not match the actual colour due to printing limitations. **Conditions Apply. **Warranty Extended for Engine, TI System, ABS System and Electrical including Wiring Harness. 5 years warranty is applicable only in case of purchase of Yamaha protection plus policy during validity period, please refer the protection plus policy for details.
Yamaha Motor India Sales Pvt. Ltd, ANDR Tower - 5th Floor, Door No. 3/311, Raju Gandhi Salai (OMR), Mettakkuppam, Chennai - 600 097
Phone: 044 3614 7040, Toll Free No: 1800 420 1600, Email: info@yamaha-motor-india.com, www.yamaha-motor-india.com



STREAK AHEAD WITH RED!
R15
Versicraft
ABS
DUAL CHANNEL

The call of
the **BLUE**



BS VI Compliant 155cc LC4V SOHC FI Engine
This liquid-cooled single overhead camshaft fuel injection engine churns out 18.6PG@10000rpm and 14.1Nm@8500rpm. Features an advanced die-cast aluminium (DIASi) cylinder with outstanding cooling performance.



Deltabox Frame
The new R15 V3.0 adopts a new Deltabox frame with superb rigidity balance. With a Deltabox frame, the top and bottom of the head pipe and the pivot points form a triangle, hence the "Deltabox" gives it excellent rigidity balance.

Assist and Slipper Clutch
Enables smooth down shifting that mitigates the effects of engine braking during deceleration.



Variable Valve Actuation (VVA)
The first-over high performance VVA system that provides power & torque in the entire rev range.



6-speed Transmission
Now shift gears without worrying about economy. The new R15 V3.0 6-speed transmission allows to cruise at low RPM even in higher gears thus saving fuel without missing on the thrill.

**Perfect racing lineage,
for the perfect racing line.**

The original supersport is back! Packed with advanced Yamaha technology, precision engineered to deliver the authentic racing experience that you crave. Born of Yamaha's racing DNA that shaped legends like the M1, the R1 and the R-series, the R15 lives up to its legacy of challenging spirit boldly. Take a ride and discover what makes the R badge the most respected – on the road and on the track!



20mm Lower Rear Seat*
Comfortable pillion position with ease of access.

140mm Super Wide Radial Rear Tire
140/70R17M/C 66H radial tire has been adopted at the rear with flexible side walls for better grip while cornering and superior shock absorbing capacity to ensure a more comfortable ride.



Multi-function LCD Instrument Cluster with Gear Shift Indicator
Opens with a personalized string of animated text. Keeps you informed of all the essentials: gear shift and gear position indicator, VVA indicator, in addition to speed, tachometer and trip meter.



LED Headlights
While the sharp design assists in overall airflow, the slim twin-eye LED headlights offers efficient lighting even for night rides.



Dual Channel ABS
202mm front and 220mm rear disc brakes with Anti-lock Braking System (ABS) gives greater control and ability to steer even while braking hard.



Side Stand Engine Cut Off Switch
Prevents unintentional engine start. When switch is on, the motorcycle will not start till the side stand is retracted.

*compared to R15 Ver.2.0